

# TECHNICAL DATA SHEET

## ONE COMPONENT SEALANT "GULBUVE"



Developed: 22.03.2012

Latest changes: 01.08.2013

Version 2

Name of the product: **One component sealant "Guļbūve"**

### 1. IDENTIFICATION OF MIXTURE AND COMPANY

#### 1.1. Product identification

**Name of the product** One component sealant "Guļbūve"

**1.2. Types of using mixture and those not suggested for the usage** Sealant for sealing logs' joints, gaps and breaks of wood log buildings, as well as sealing wood facade seams.

**1.3. Information on safety data sheet supplier** **Producer:**  
Ltd "STAFOR"  
Kuldīgas street 53a,  
Rīga, Latvia, LV-1046  
Ph./Fax: +371 67603399  
E-mail: info@stafor.lv

**1.4. Phone number for emergency situations** State Fire and Rescue Service: 112 (24h)  
State Toxicology Centre: (+371) 67042473 (24h)

### 2. PHYSICAL AND CHEMICAL PROPERTIES

#### 2.1. Information on basic physical and chemical properties

<b>General information:</b>	
Aggregate state:	Thixotrope pasty mass.
Color:	In color of used pigments.
Scent:	Specific of linseed oil
Average particle size:	No data
Surface film forming:	~4 hours (23°C, humidity 50%)
Drying speed:	~2-3mm/24h (23°C, humidity 50%)
Shrink:	≤1%
Elasticity:	≥300%
Conditional strength at break:	No data
Relative elongation at break:	No data
Modulus of elasticity at 100% elongation:	No data
Application temperature:	+1°C till +50°C
Usage temperature:	-50°C till +70°C
<b>Recommended characteristics of joint (vertical structures)</b>	
Allowable deformation (from the nominal size):	±20%
Depth of joint	5 - 15mm
Width of joint	10 - 30mm
Joint width to depth ratio	2:1
<b>The most essential information on health protection, safety and environment protection:</b>	
Product's pH:	Not detectable, does not characterize the product



**SIA STAFOR**  
Reģ. Nr.: LV 40103520315  
Biroja adr.: Kuldīgas iela 53a, Rīga, Latvija  
Internets: [www.stafor.lv](http://www.stafor.lv) info@stafor.lv

Tālr.: +371 67603399  
Fax: +371 67603399  
Mob.: +371 29219954  
+371 26408999

Banka: SWEDBANK  
SWIFT: HABALV22  
Konts: LV83HABA0551032881717

**TECHNICAL DATA SHEET**  
**ONE COMPONENT SEALANT "GULBUVE"**



Developed: 22.03.2012

Latest changes: 01.08.2013

Version 2

Name of the product: **One component sealant "Gulbūve"**

Boiling point:	No data
Ignition temperature:	No data
Combustibility:	No data
Ingredients that can explode:	No data
Oxidizing/reducing properties:	No data
Vapor pressure	No data
Relative density:	~ 1,4 g/cm <sup>3</sup>
Dissolution in water:	Insoluble
Dissolution:	No data
Water/n-octanol partition coefficient:	No data
Dynamic viscosity	No data
Viscosity	No data
Vapor density	No data
Evaporation speed	No data



**SIA STAFOR**

Reģ. Nr: LV 40103520315

Biroja adr.: Kuldīgas iela 53a, Rīga, Latvija

Internets: [www.stafor.lv](http://www.stafor.lv) info@stafor.lv

Tālr.: +371 67603399

Fax: +371 67603399

Mob.: +371 29219954

+371 26408999

Banka: SWEDBANK

SWIFT: HABALV22

Konts: LV83HABA0551032881717